

extract_and_clean_continent_traits.R

June 18, 2026

Contents

extract_and_clean_continent_traits 1

Index 3

extract_and_clean_continent_traits

Extract and Clean Trait Data for One Continental Unit

Description

Extracts raw trait data from VegVault for a single continental bounding box, removes incomplete records, and translates numeric taxon IDs to taxon names. Optionally prints progress messages.

Usage

```
extract_and_clean_continent_traits(  
  data_continental_rows,  
  vec_trait_domain_names,  
  path_to_vegvault = here::here("Data/Input/VegVault.sqlite"),  
  verbose = TRUE  
)
```

Arguments

data_continental_rows

A single-row data frame (one continental unit from the spatial grid) with columns 'scale_id', 'x_min', 'x_max', 'y_min', and 'y_max'.

vec_trait_domain_names

A non-empty character vector of trait domain names to extract (e.g. 'c("Specific leaf area (SLA)", "Plant height vegetative")').

path_to_vegvault

A single character string giving the path to the VegVault SQLite database (default: 'here::here("Data/Input/VegVault.sqlite")').

verbose

A single logical value. If 'TRUE' (default), progress messages are printed via 'cli::cli_inform()'. Set to 'FALSE' to suppress all console output.

Details

The function performs the following steps:

1. Validates all input arguments.
2. Derives the bounding-box limits and scale identifier from 'data_continental_rows'.
3. Calls [extract_traits_from_vegvault()] to retrieve raw records.
4. Calls [clean_raw_trait_data()] to drop incomplete rows.
5. Calls [resolve_trait_taxon_ids()] to replace numeric IDs with taxon names.
6. Returns the final tibble with taxon-name columns only.

Value

A tibble with columns 'taxon_name', 'trait_domain_name', 'trait_name', and 'trait_value', containing the cleaned and ID-resolved trait records for the supplied continental unit.

See Also

[extract_traits_from_vegvault()], [clean_raw_trait_data()], [resolve_trait_taxon_ids()]

Index

`extract_and_clean_continent_traits`, [1](#)