

interpolate_data.R

June 18, 2026

Contents

interpolate_data	1
Index	3

interpolate_data	<i>Interpolate Data</i>
------------------	-------------------------

Description

Interpolates data over a specified age range and timestep using a method.

Usage

```
interpolate_data(  
  data = NULL,  
  by = "dataset_name",  
  age_var = "age",  
  value_var = "value",  
  method = "linear",  
  rule = 1,  
  ties = mean,  
  age_min = 0,  
  age_max = 12000,  
  timestep = 500,  
  n_cores = 1,  
  verbose = TRUE  
)
```

Arguments

data	A data frame containing the data to be interpolated.
by	A character vector of column name(s) to group by when nesting data for interpolation (default: "dataset_name").
age_var	Name of the age variable column (default: "age").
value_var	Name of the value variable column (default: "value").

<code>method</code>	Interpolation method to use (default: "linear").
<code>rule</code>	Integer specifying the extrapolation rule (default: 1).
<code>ties</code>	Function to handle tied values (default: 'mean').
<code>age_min</code>	Minimum age for interpolation (default: 0).
<code>age_max</code>	Maximum age for interpolation (default: 12000).
<code>timestep</code>	Timestep for interpolation (default: 500).
<code>n_cores</code>	Number of cores to use for interpolation. Use '1' for sequential 'purrr::map()' execution, or a value greater than '1' for parallel 'furrr::future_map()' execution.
<code>verbose</code>	Logical. If 'TRUE' (default), progress bars are displayed where supported.

Details

Nests data by dataset and taxon. It interpolates with 'stats::approx()' and returns the interpolated data in a flat format.

Value

A data frame with interpolated values, including dataset name, taxon, age, and value columns.

See Also

[stats::approx()]

Index

`interpolate_data`, [1](#)