

render_trait_quality_control_report.R

August 7, 2026

Contents

render_trait_quality_control_report	1
Index	3

render_trait_quality_control_report
<i>Render a Trait Quality-Control Report</i>

Description

Renders 'trait_quality_control_report.qmd' to a dated PDF for one trait domain (or for all domains when 'trait_domain_filter' is 'NULL'), moves the rendered file from the Quarto docs output directory to 'path_report_directory', and compresses it in-place with 'qpdf::pdf_compress()'.

The output filename follows one of two patterns depending on 'trait_domain_filter': - 'NULL': 'trait_quality_control_report_Sys.Date().pdf' - character: 'trait_qc_<slug>_Sys.Date().pdf' where '<slug>' is 'trait_domain_filter' with all non-alphanumeric characters replaced by underscores.

Usage

```
render_trait_quality_control_report(  
  trait_domain_filter = NULL,  
  path_report_directory = here::here("Outputs/Reports"),  
  path_report_source = here::here("R", "03_Supplementary_analyses", "Diagnostics",  
    "Data_processing", "Traits", "Quality_control", "trait_quality_control_report.qmd"),  
  path_render_directory = here::here("docs", "R", "03_Supplementary_analyses",  
    "Diagnostics", "Data_processing", "Traits", "Quality_control"),  
  maximum_pages = NULL,  
  minimum_taxonomic_records = 5L,  
  verbose = TRUE  
)
```

Arguments

trait_domain_filter
Character scalar or 'NULL'. When 'NULL', all domains are rendered into a single PDF. When a character scalar, only taxa from that trait domain are included. Default: 'NULL'.

<code>path_report_directory</code>	Character scalar. Directory where the compressed PDF is saved. Default: <code>'here::here("Outputs/Report")'</code> .
<code>path_report_source</code>	Character scalar. Path to the Quarto source document. Default: <code>'here::here("R", "03_Supplementary_analyses", "Diagnostics", "Data_processing", "Traits", "Quality_control", "trait_quality_control_report.qmd")'</code> .
<code>path_render_directory</code>	Character scalar. Directory that Quarto writes its output to before the file is moved. Default: <code>'here::here("docs", "R", "03_Supplementary_analyses", "Diagnostics", "Data_processing", "Traits", "Quality_control")'</code> .
<code>maximum_pages</code>	Positive integer scalar or <code>'NULL'</code> . Maximum number of pages to render. When <code>'NULL'</code> (default) there is no cap.
<code>minimum_taxonomic_records</code>	Positive integer scalar. Minimum records per taxon required for inclusion in the taxonomic comparison panel. Default: <code>'5L'</code> .
<code>verbose</code>	Logical. If <code>'TRUE'</code> (default), a progress message with the output path is printed to the console via <code>'cli::cli_inform()'</code> . A warning is emitted via <code>'cli::cli_warn()'</code> if the rendered file cannot be found.

Details

The function calls `'quarto::quarto_render()'` with `'execute_params'` set to `'maximum_pages'`, `'minimum_taxonomic_records'`, and `'trait_domain_filter'`. The rendered file is expected at `'file.path(path_render_directory, <output_filename>)'`. If found it is moved to `'path_report_directory'` and compressed; if not found a warning is emitted and nothing is moved.

Value

Invisible `'NULL'`. Called for its side effects: rendering and moving a PDF to `'path_report_directory'`.

See Also

`[write_trait_quality_control_report()]`

Index

`render_trait_quality_control_report`, [1](#)