

build_r_architecture_dependency_map.R

August 31, 2026

Contents

build_r_architecture_dependency_map	1
---	---

Index	3
--------------	----------

build_r_architecture_dependency_map
<i>Build R Architecture Dependency Map</i>

Description

Builds deterministic Markdown describing repository R ownership, pipeline/profile/store relationships, persisted contracts, and exceptions.

Usage

```
build_r_architecture_dependency_map(  
  data_scripts,  
  data_functions,  
  data_contracts,  
  data_manifests,  
  data_exceptions  
)
```

Arguments

data_scripts	Script-path inventory data frame.
data_functions	Function inventory data frame.
data_contracts	Persisted-contract inventory data frame.
data_manifests	Manifest-derived profile and target inventory data frame.
data_exceptions	Maintained architecture-exception ledger.

Value

Character vector containing the architecture map Markdown.

Examples

```
build_r_architecture_dependency_map(  
  data_scripts = tibble::tibble(  
    classification = "main_analysis",  
    migration_status = "migrated"  
  ),  
  data_functions = tibble::tibble(  
    current_path = "R/Functions/example.R",  
    intended_path = "R/Functions/example.R",  
    migration_status = "baseline_recorded",  
    callers = "R/Pipelines/_pipes/pipe_segment_example.R"  
  ),  
  data_contracts = tibble::tibble(  
    contract_type = "literal_target",  
    contract_scope = "persisted_internal"  
  ),  
  data_manifests = tibble::tibble(  
    profile_id = "example",  
    profile_role = "smoke",  
    pipeline_id = "example",  
    pipeline_script = "R/Pipelines/example.R",  
    target_store = "Data/targets/example",  
    manifest_target_count = 1L  
  ),  
  data_exceptions = tibble::tibble(  
    exception_id = character(),  
    owner_issue = character(),  
    expiry_issue = character()  
  )  
)
```

Index

`build_r_architecture_dependency_map`, [1](#)