

evaluate_sjsdm_fold_predictions.R

August 31, 2026

Contents

evaluate_sjsdm_fold_predictions 1

Index 3

evaluate_sjsdm_fold_predictions
Evaluate sjSDM Predictions Within Cross-Validation Folds

Description

Calculates model and prevalence-null prediction metrics separately within each repeat, fold, and taxon.

Usage

```
evaluate_sjsdm_fold_predictions(data_predictions = NULL, epsilon = 1e-06)
```

Arguments

data_predictions	Long selected-candidate OOF prediction table returned in the data-prediction element of [run_sjsdm_selected_candidate_folds()].
epsilon	Probability clipping tolerance passed to [evaluate_binary_log_loss()]. Defaults to 1e-6.

Details

Unlike [evaluate_sjsdm_cross_validated_predictions()], this function never pools probabilities from separately fitted fold models. Model and null predictions are evaluated independently, so an unavailable model prediction does not suppress a valid prevalence-null diagnostic.

Value

Tibble with one row per repeat, fold, taxon, prediction source, and metric. Prediction sources are model and prevalence_null; metrics are Tjur R2, AUC, binary log loss, Brier score, calibration intercept, and calibration slope.

Examples

```
## Not run:  
evaluate_sjsdm_fold_predictions(  
  data_predictions = data_predictions  
)  
  
## End(Not run)
```

Index

`evaluate_sjsdm_fold_predictions`, [1](#)