

load_model_tuning_parameters.R

August 31, 2026

Contents

load_model_tuning_parameters 1

Index 2

load_model_tuning_parameters
Get Model Tuning Parameters

Description

Reads model-fitting parameters for one analysis, spatial unit, and resolution from the model tuning CSV catalogue.

Usage

```
load_model_tuning_parameters(  
  analysis_id,  
  scale_id,  
  resolution_id,  
  dir = here::here("Data/Input/Model_tuning")  
)
```

Arguments

analysis_id	A single non-empty character string identifying the analysis family, such as "paleo_spatial" or "modern_spatial".
scale_id	A single non-empty character string identifying the spatial unit. Must match exactly one row in the selected tuning file.
resolution_id	A single character string identifying the model resolution. "genus" reads the *_genus.csv file, "family" reads the *_family.csv file, and "functional_type", "ft_paleo", and "ft_modern" read the *_ft.csv file.
dir	Directory containing model tuning CSV files. Default: here::here("Data/Input/Model_tuning").

Value

A named list with 'n_iter', 'n_step_size', 'n_sampling', 'n_samples_anova', and 'n_early_stopping'. Missing 'n_step_size' and 'n_early_stopping' values are returned as 'NULL'.

Index

`load_model_tuning_parameters`, [1](#)