

prepare_decomposition_fold_input.R

August 31, 2026

Contents

prepare_decomposition_fold_input 1

Index 3

prepare_decomposition_fold_input
Prepare Decomposition Fold Input

Description

Rebuilds model input for one route and one train/test split using fold-local response filtering and train-only predictor scaling.

Usage

```
prepare_decomposition_fold_input(  
  route = NULL,  
  inputs = NULL,  
  train_ids = NULL,  
  test_ids = NULL  
)
```

Arguments

route	One-row route data frame or named list.
inputs	List returned by ‘load_decomposition_diagnostic_inputs()’.
train_ids	Character vector of training sample row names.
test_ids	Character vector of test sample row names.

Details

This route-specific wrapper delegates training-only MEM construction and held-out projection to ‘prepare_fold_spatial_predictors()’, then delegates common response filtering, alignment, and predictor scaling to ‘prepare_model_fold_input()’.

Value

Named list returned by ‘prepare_model_fold_input()’, including training input, test input, test observations, a taxon mapping, model-input diagnostics, and fold-local spatial diagnostics.

Examples

```
## Not run:
data_fold <-
  prepare_decomposition_fold_input(
    route = data_route,
    inputs = list_decomposition_inputs,
    train_ids = vec_train_ids,
    test_ids = vec_test_ids
  )

## End(Not run)
```

Index

`prepare_decomposition_fold_input`, [1](#)