

# run\_sjsdm\_tuning\_fold\_candidates.R

August 31, 2026

## Contents

|                                            |                   |
|--------------------------------------------|-------------------|
| run_sjsdm_tuning_fold_candidates . . . . . | <a href="#">1</a> |
| <b>Index</b>                               | <a href="#">3</a> |

---

|                                  |                                                 |
|----------------------------------|-------------------------------------------------|
| run_sjsdm_tuning_fold_candidates |                                                 |
|                                  | <i>Run sjSDM Tuning Candidates for One Fold</i> |

---

## Description

Prepares one fold once, then fits, predicts, and scores every regularization candidate while preserving failures as compact status rows.

## Usage

```
run_sjsdm_tuning_fold_candidates(  
  data_candidates = NULL,  
  list_fold_context = NULL,  
  prepare_fold_function = NULL,  
  fit_function = NULL,  
  predict_function = NULL,  
  score_function = score_sjsdm_tuning_predictions,  
  seed = 900723L,  
  epsilon = 1e-06,  
  retain_prediction_cache = FALSE  
)
```

## Arguments

`data_candidates`  
Candidate table returned by [build\_sjsdm\_regularization\_candidates()].

`list_fold_context`  
Fold metadata returned by [build\_sjsdm\_tuning\_fold\_context()].

`prepare_fold_function`, `fit_function`, `predict_function`, `score_function`  
Injectable fold preparation, fit, prediction, and scoring functions documented by [run\_sjsdm\_tuning\_candidates()].

|                                      |                                                                                                                                    |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| <code>seed</code>                    | Non-negative base integer used to derive candidate fit and score seeds.                                                            |
| <code>epsilon</code>                 | Probability clipping tolerance passed to <code>[score_sjsdm_tuning_predictions()]</code> .                                         |
| <code>retain_prediction_cache</code> | Logical. When true, return compact prepared-fold metadata and candidate probability matrices alongside the unchanged tuning table. |

**Value**

Compact candidate-by-fold tuning table with metrics and structured status. When ‘`retain_prediction_cache`’ is true, returns a named list containing that table and a compact fold prediction cache without fitted model objects.

# Index

run\_sjsdm\_tuning\_fold\_candidates, [1](#)