

# score\_sjsdm\_tuning\_predictions.R

August 31, 2026

## Contents

|                                          |          |
|------------------------------------------|----------|
| score_sjsdm_tuning_predictions . . . . . | 1        |
| <b>Index</b>                             | <b>2</b> |

---

|                                       |
|---------------------------------------|
| score_sjsdm_tuning_predictions        |
| <i>Score sjSDM Tuning Predictions</i> |

---

## Description

Calculates compact held-out binomial tuning metrics from aligned observed and predicted matrices.

## Usage

```
score_sjsdm_tuning_predictions(  
  data_observed = NULL,  
  data_predicted = NULL,  
  object = NULL,  
  data_test_input = NULL,  
  epsilon = 1e-06  
)
```

## Arguments

|                         |                                                                                                                                                      |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| data_observed           | Binary numeric matrix of held-out observations.                                                                                                      |
| data_predicted          | Numeric matrix of held-out probabilities with matching dimensions and dimnames. Missing prediction dimnames inherit observation dimnames.            |
| object, data_test_input | Optional fitted object and test input accepted for compatibility with the tuning-runner scoring callback. Marginal probability scoring ignores them. |
| epsilon                 | Probability clipping tolerance strictly between zero and ‘0.5’.                                                                                      |

## Value

One-row tibble with retained taxa, response-value count, total and per-response negative log likelihood, and macro AUC.

# Index

score\_sjsdm\_tuning\_predictions, [1](#)