# diagnose_sjsdm_cv_preparation_endpoints.R

October 22, 2026

## Contents

diagnose_sjsdm_cv_preparation_endpoints . . . . . 1

**Index** **3**

---

`diagnose_sjsdm_cv_preparation_endpoints`
*Diagnose sjSDM CV Preparation Endpoints*

---

### Description

Diagnoses whether requested prepared-fold targets exist, have successful metadata and content hashes, and can be read from a targets store.

### Usage

```
diagnose_sjsdm_cv_preparation_endpoints(
  store_path = NULL,
  target_names = NULL,
  load_metadata_function = load_targets_store_metadata,
  read_target_function = targets::tar_read_raw,
  file_exists_function = base::file.exists
)
```

### Arguments

| | |
|---|---|
| `store_path` | Character scalar identifying the targets store. |
| `target_names` | Unique non-empty character vector of prepared-fold target names. |
| `load_metadata_function` | Injectable target-metadata loader. |
| `read_target_function` | Injectable raw target reader. |
| `file_exists_function` | Injectable existence check for the endpoint's serialized object. A 'qs' fallback error proves incompatibility only when that object exists. |

## Details

Endpoint statuses are ‘prepared‘, ‘missing‘, ‘errored‘, ‘unreadable‘, or ‘cache_format_incompatible‘. The last status is reserved for legacy ‘qs‘ objects that current ‘qs2‘-based targets installations cannot read.

## Value

A tibble with one row per requested target and its endpoint status, data hash, and diagnostic message.

# Index

diagnose_sjsdm_cv_preparation_endpoints,
        1