is_sjsdm_cv_prepared_folds_current.R

October 22, 2026

Contents

is_sjsdm_cv_prepared_folds_current 1

Index **3**

`is_sjsdm_cv_prepared_folds_current`
Test Prepared Fold Content Against Current Preparation Code

Description

Reconstructs folds in memory and requires exact analytical equality. This permits error-only code changes without rewriting operational runtimes in cached folds or invalidating successful fitting descendants.

Usage

```
is_sjsdm_cv_prepared_folds_current(
  store_path,
  target_name,
  read_target_function = targets::tar_read_raw,
  prepare_fold_function = prepare_sjsdm_cross_validation_fold,
  load_metadata_function = targets::tar_meta
)
```

Arguments

`store_path`, `target_name`
: Existing store and one prepared-fold endpoint.

`read_target_function`, `prepare_fold_function`
: Injectable cached target reader and current fold-preparation adapter.

`load_metadata_function`
: Injectable target metadata reader for current input-name resolution.

Details

Call only after every upstream input and configuration has been verified. This function does not execute targets, fit models, or write to stores.

Value

A logical scalar; unreadable inputs and reconstruction errors fail.

Examples

```
## Not run:
is_sjsdm_cv_prepared_folds_current(store, "list_sjsdm_prepared_tuning_folds")

## End(Not run)
```

Index

is_sjsdm_cv_prepared_folds_current, 1