load_sjsdm_tuning_summaries.R

October 22, 2026

Contents

load_sjsdm_tuning_summaries 1

Index **3**

`load_sjsdm_tuning_summaries`
Collect sjSDM Tuning Summaries

Description

Reads compact resolution-specific tuning summaries from isolated unit targets stores for a shared tier-selection stage.

Usage

```
load_sjsdm_tuning_summaries(
  store_paths = NULL,
  resolution_ids = NULL,
  target_prefix = "list_sjsdm_cv_tuning_artifact",
  target_names = NULL,
  read_target_function = targets::tar_read_raw,
  file_unit_requests = NULL
)
```

Arguments

`store_paths`	Non-empty character vector of unit targets-store paths.
`resolution_ids`	Non-empty character vector of mapped model-resolution identifiers.
`target_prefix`	Non-empty character scalar placed before each resolution identifier. Defaults to the existing public tuning-summary target prefix. Explicit round prefixes allow the tier store to collect one staged round at a time.
`target_names`	Optional character vector paired with ‘resolution_ids‘. When supplied, reads these exact public target names instead of constructing suffixed names.
`read_target_function`	Injectable target reader. Defaults to [targets::tar_read_raw()].

`file_unit_requests`
: Optional explicit CSV of verified ‘source_store‘ and ‘target_name‘ pairs. When present, tier pooling requests only these eligible pairs. Missing files preserve the legacy Cartesian request contract.

Value

Bound tuning-summary tibble with ‘source_store‘ and ‘resolution_id‘ provenance columns. Every requested store-resolution target must be readable. The function aborts with the failed store and target when evidence is incomplete.

Examples

```
## Not run:
load_sjsdm_tuning_summaries(
  store_paths = c("store_a", "store_b"),
  resolution_ids = c("genus", "family")
)

## End(Not run)
```

Index

load_sjsdm_tuning_summaries, 1