run_sjsdm_likelihood_sequence.R

October 22, 2026

Contents

run_sjsdm_likelihood_sequence 1

Index **3**

`run_sjsdm_likelihood_sequence` *Run Ordered Conditional Likelihood Calls with Progress*

Description

Preserves sjSDM's iteration order and simplification while reporting each taxon's start, completion, and elapsed time without drawing random numbers.

Usage

```
run_sjsdm_likelihood_sequence(
  X,
  FUN,
  ...,
  simplify = TRUE,
  USE.NAMES = TRUE,
  verbose = TRUE,
  progress_state = NULL
)
```

Arguments

`X`	Ordered indices supplied by sjSDM's conditional likelihood helper.
`FUN`	Per-taxon likelihood function supplied by sjSDM.
`...`	Additional arguments forwarded unchanged to FUN.
`simplify, USE.NAMES`	Simplification controls from the upstream call.
`verbose`	Logical; print timestamped likelihood progress.
`progress_state`	Optional private environment tracking ANOVA pass names.

Value

An array or list with the same values as the upstream mapping.

Examples

```
run_sjsdm_likelihood_sequence(
  X = 1:3,
  FUN = base::identity,
  verbose = FALSE
)
```

Index

run_sjsdm_likelihood_sequence, 1