validate_sjsdm_cv_preparation_freshness.R

October 22, 2026

Contents

validate_sjsdm_cv_preparation_freshness 1

Index **3**

`validate_sjsdm_cv_preparation_freshness`
Validate Current Calibration Preparation Dependencies

Description

Blocks stale preparation without executing analytical pipeline targets.

Usage

```
validate_sjsdm_cv_preparation_freshness(
  pipeline_script,
  store_path,
  target_names,
  manifest_function = targets::tar_manifest,
  network_function = targets::tar_network,
  outdated_function = targets::tar_outdated,
  read_target_function = targets::tar_read_raw,
  verify_folds_function = is_sjsdm_cv_prepared_folds_current,
  verify_mapping_function = is_sjsdm_cv_preparation_mapping_current,
  load_metadata_function = targets::tar_meta
)
```

Arguments

`pipeline_script`, `store_path`
: Current pipeline definition and its existing unit store.

`target_names`
: Prepared input endpoints whose upstream dependencies must be current.

`manifest_function`, `network_function`, `outdated_function`
: Injectable public targets inspection functions.

`read_target_function`
: Injectable cached target reader for configuration comparisons.

`verify_folds_function`
: Injectable exact in-memory proof for preparation-only code differences.

`verify_mapping_function`
: Injectable exact in-memory proof for the known pure community mapper.

`load_metadata_function`
: Injectable public cached-target metadata reader. Missing dependency records block validation before shortcut inspection; analytical work is not run.

Details

Always-cued configuration commands are read-only and compared exactly with cached values. Other always-cued ancestors are rejected. All remaining ancestors are checked individually with shortcut inspection, avoiding the false propagation of unchanged always-cued configuration into their users. The two known shared-memory interpolation handles are operational wrappers; their durable input ancestors are inspected instead of creating new handles. Required cached dependency records are checked before shortcut inspection, which cannot bootstrap newly introduced targets without metadata.

Value

Invisibly, ‘NULL‘ after successful validation.

Examples

```
## Not run:
validate_sjsdm_cv_preparation_freshness(
  "R/Pipelines/pipeline.R", "Data/targets/store", "prepared_folds"
)

## End(Not run)
```

Index

validate_sjsdm_cv_preparation_freshness,
        1