validate_sjsdm_cv_production_calibration.R

October 22, 2026

Contents

validate_sjsdm_cv_production_calibration 1

Index **3**

`validate_sjsdm_cv_production_calibration`
Validate Calibration Evidence Before Production Tuning

Description

Rechecks current representative preparation and saved calibration inputs before a production tier can launch tuning. A published label is not proof.

Usage

```
validate_sjsdm_cv_production_calibration(
  profile_id,
  data_representatives = NULL,
  validate_preparation_function = validate_sjsdm_cv_preparation_freshness,
  validate_evidence_function = validate_sjsdm_cv_calibration_evidence,
  read_target_function = targets::tar_read_raw,
  load_evidence_function = qs2::qs_read
)
```

Arguments

`profile_id`	Main spatial or paleo-temporal configuration profile.
`data_representatives`	Optional representative inventory. Defaults to the published CSV.
`validate_preparation_function`, `validate_evidence_function`	Injectable preparation freshness and calibration compatibility checks.
`read_target_function`, `load_evidence_function`	Injectable cached production target and calibration evidence readers.

Value

Invisibly, 'NULL' when the required evidence is compatible.

Examples

```
## Not run:
validate_sjsdm_cv_production_calibration("project_modern_spatial_local")

## End(Not run)
```

Index

validate_sjsdm_cv_production_calibration,
        1