

R documentation

of all in
'C:/Users/ondre/AppData/Local/Temp/codex_prepare_fold_spatial_doc/prepare_fold_spatial_predictors.R'
June 30, 2026

Contents

prepare_fold_spatial_predictors	1
Index	3

prepare_fold_spatial_predictors	
<i>Prepare Fold-Local Spatial Predictors</i>	

Description

Computes Moran eigenvector predictors from training locations or samples only and projects them to held-out samples with the production IDW path.

Usage

```
prepare_fold_spatial_predictors(  
  data_coords_projected = NULL,  
  data_sample_ids = NULL,  
  train_ids = NULL,  
  test_ids = NULL,  
  spatial_mode = NULL,  
  n_mev = NULL,  
  compute_spatial_function = compute_spatial_mev,  
  compute_spatiotemporal_function = compute_spatiotemporal_mev,  
  interpolate_spatial_function = interpolate_mev_to_grid,  
  interpolate_spatiotemporal_function = interpolate_st_mev_to_grid  
)
```

Arguments

`data_coords_projected`
Data frame with site row names and 'coord_x_km' and 'coord_y_km' columns.

`data_sample_ids`
Data frame containing 'dataset_name' and 'age' for all candidate samples.

`train_ids, test_ids` Disjoint sample identifiers in "dataset_name__age" format. Locations represented by the two partitions must also be disjoint.

`spatial_mode` Character scalar. Supported values are "spatial" and "spatiotemporal".

`n_mev` Positive integer giving the requested number of Moran eigenvectors.

`compute_spatial_function, compute_spatiotemporal_function` Functions used to compute 2-D and spatiotemporal Moran eigenvectors.

`interpolate_spatial_function, interpolate_spatiotemporal_function` Functions used to project training Moran eigenvectors to held-out samples.

Value

Named list with unscaled training and held-out spatial predictor data frames plus fold-level spatial diagnostics.

Examples

```
## Not run:
list_spatial_fold <-
  prepare_fold_spatial_predictors(
    data_coords_projected = data_coords,
    data_sample_ids = data_samples,
    train_ids = vec_train_ids,
    test_ids = vec_test_ids,
    spatial_mode = "spatial",
    n_mev = 3L
  )

## End(Not run)
```

Index

`prepare_fold_spatial_predictors`, [1](#)