

load_latest_functional_type_classification.R

August 7, 2026

Contents

load_latest_functional_type_classification	1
Index	3

load_latest_functional_type_classification	
<i>Load Latest Functional-Type Classification</i>	

Description

Loads the most recent FT classification file for a given continental unit from 'Data/Processed/Traits/'. The file is produced by 'pipe_segment_traits_ft_clustering' in 'pipeline_traits_reference.R' and named 'data_functional_type_classification_continent_id_YYYY-MM-DD.qs'.

Usage

```
load_latest_functional_type_classification(  
  continent_id,  
  path_classification_directory = here::here("Data/Processed/Traits")  
)
```

Arguments

continent_id	A single non-empty character string identifying the continental unit (e.g. "eu-rope", "america", "asia"). Must match exactly with the 'scale_id' used when the FT classification was saved.
path_classification_directory	A single character string giving the directory that contains the FT classification '.qs' files. Default: 'here::here("Data/Processed/Traits")'.

Details

The function delegates path selection to [resolve_functional_type_classification_path()] and file loading to [load_functional_type_classification()].

Value

A tibble with two columns:

taxon_name Character. Taxon names resolved to finest available rank, matching the ‘taxon_name’ column in the global trait table.

functional_type Integer. Cluster label (1..‘functional_type_group_count’) assigned for this continental unit.

See Also

[assign_functional_type_clusters()], [resolve_functional_type_classification_path()], [load_functional_type_classification]

Index

load_latest_functional_type_classification,
1