

build_sjsdm_tuning_schedule.R

August 10, 2026

Contents

build_sjsdm_tuning_schedule	1
Index	3

build_sjsdm_tuning_schedule
<i>Build an sjSDM Tuning Schedule</i>

Description

Validates exhaustive or staged cross-validation tuning settings and builds the deterministic repeat-level candidate budget used by every model pipeline.

Usage

```
build_sjsdm_tuning_schedule(  
  tuning_strategy = NULL,  
  n_candidates = NULL,  
  repeat_ids = NULL,  
  survivor_counts = NULL  
)
```

Arguments

tuning_strategy	Character scalar. Either "exhaustive" or "staged".
n_candidates	Positive integer number of regularization candidates.
repeat_ids	Unique positive integer repeat identifiers in execution order.
survivor_counts	Integer counts retained after each non-final staged round. Ignored for exhaustive tuning.

Value

Tibble with one row per tuning round and columns 'tuning_strategy', 'strategy_version', 'round_id', 'repeat_id', 'n_candidates_entering', and 'n_candidates_surviving'.

Examples

```
build_sjsdm_tuning_schedule(  
  tuning_strategy = "staged",  
  n_candidates = 8L,  
  repeat_ids = 1:3,  
  survivor_counts = c(4L, 2L)  
)
```

Index

`build_sjsdm_tuning_schedule`, [1](#)