

# make\_cross\_validation\_branch\_assignments.R

August 10, 2026

## Contents

|                                                    |          |
|----------------------------------------------------|----------|
| make_cross_validation_branch_assignments . . . . . | 1        |
| <b>Index</b>                                       | <b>3</b> |

---

|                                                 |
|-------------------------------------------------|
| make_cross_validation_branch_assignments        |
| <i>Make Cross-Validation Branch Assignments</i> |

---

## Description

Reuses a shared pre-resolution assignment for a response-resolution branch when coverage and balance remain valid, otherwise recalibrates that branch.

## Usage

```
make_cross_validation_branch_assignments(  
  data_locations = NULL,  
  data_fold_resolution = NULL,  
  data_shared_assignments = NULL,  
  target_locations_per_cell = 5,  
  grid_size_multipliers = 2^base::seq(-2, 2),  
  n_repeats = 1L,  
  occupancy_criterion = "median",  
  lower_quantile_probability = 0.25,  
  max_fold_location_difference = 1L,  
  max_fold_sample_difference = Inf,  
  seed = 900723L  
)
```

## Arguments

`data_locations` Branch location table returned by [make\_cross\_validation\_location\_table()].  
`data_fold_resolution` One-row branch table returned by [resolve\_cross\_validation\_fold\_count()].

`data_shared_assignments`

Assignment table built from the shared pre-resolution sample universe.

`target_locations_per_cell, grid_size_multipliers, n_repeats`

`occupancy_criterion, lower_quantile_probability, max_fold_location_difference, max_fold_sample_d`

Grid-calibration and assignment controls used only when branch fallback is required.

## Value

Assignment tibble with the stable assignment schema. ‘assignment\_source’ is “shared\_pre\_resolution”, “branch\_fallback”, or “branch\_no\_holdout”.

## Examples

```
data_locations <-
  tibble::tibble(
    location_id = base::letters[1:6],
    coord_x_km = base::seq_len(6L),
    coord_y_km = base::seq_len(6L),
    n_samples = base::rep(1L, 6L),
    row_indices = base::as.list(base::seq_len(6L))
  )
data_resolution <-
  resolve_cross_validation_fold_count(6L, 5L)
data_shared <-
  make_leave_one_location_out_assignments(data_locations)
make_cross_validation_branch_assignments(
  data_locations = data_locations,
  data_fold_resolution = data_resolution,
  data_shared_assignments = data_shared
)
```

# Index

make\_cross\_validation\_branch\_assignments,  
1