

save_missing_taxa_template.R

August 10, 2026

Contents

save_missing_taxa_template	1
--------------------------------------	---

Index	3
--------------	----------

save_missing_taxa_template
<i>Save the shared missing-taxa template</i>

Description

Reads the existing missing-taxa template CSV (if present), removes any entries that are now present in ‘data_classification_table’ (i.e. have since been classified), appends any new unclassified taxa, deduplicates by ‘sel_name’, and writes the result back to disk. If the file does not yet exist it is created. Nothing is written when ‘data_missing_taxa’ is empty, the file already exists, and no stale entries need to be removed.

Usage

```
save_missing_taxa_template(  
  data_missing_taxa,  
  file_missing_taxa_template = here::here("Data/Input/missing_taxa_template.csv"),  
  data_classification_table = NULL  
)
```

Arguments

- data_missing_taxa**
A tibble with columns ‘sel_name’, ‘kingdom’, ‘phylum’, ‘class’, ‘order’, ‘family’, ‘genus’, and ‘species’ (all character). Rows represent taxa that could not be classified. Pass an empty tibble (zero rows) when there are no new missing taxa.
- file_missing_taxa_template**
A length-1 character string giving the path to the CSV file. Defaults to ‘here::here("Data/Input/missing_taxa_template.csv")’.
- data_classification_table**
‘NULL’ (default) or a data frame with at least a ‘sel_name’ column. When provided, any entry already present in the existing template whose ‘sel_name’ also appears in this table is removed from the template before merging. This prevents stale entries from re-appearing after a taxon has been manually added to the auxiliary classification table.

Details

The file is only written when at least one of the following is true:

- ‘data_missing_taxa’ contains one or more rows.
- The file at ‘file_missing_taxa_template’ does not yet exist.
- ‘data_classification_table’ is not ‘NULL’ and at least one existing template entry is now classified.

Deduplication keeps the first occurrence of each ‘sel_name’.

Value

The ‘file_missing_taxa_template’ string (invisibly), so it can be used as a ‘format = "file"’ target return value in a targets pipeline.

See Also

[load_auxiliary_classification_table()], [select_unclassified_taxa()], [validate_taxa_classification_coverage()]

Index

save_missing_taxa_template, [1](#)