

extract_age_uncertainty_from_vegvault.R

August 12, 2026

Contents

extract_age_uncertainty_from_vegvault	1
Index	3

extract_age_uncertainty_from_vegvault
<i>Extract Age Uncertainty from VegVault</i>

Description

Retrieves per-sample age-model iteration data from a pre-built vaultkeepr query plan and joins the result to a caller-supplied sample-to-dataset mapping.

Usage

```
extract_age_uncertainty_from_vegvault(  
  plan,  
  data_sample_mapping,  
  verbose = TRUE  
)
```

Arguments

plan	A vaultkeepr plan object scoped to fossil pollen archive datasets, typically created by 'build_vegvault_plan()' with 'sel_dataset_type = "fossil_pollen_archive"'.
data_sample_mapping	A data frame with at least the columns 'dataset_name' and 'sample_name', used to attach dataset identifiers to the per-iteration age estimates (e.g. 'data_community_proportions').
verbose	Logical. If 'TRUE' (default), progress messages are printed to the console via 'cli'.

Details

The function performs the following steps: 1. Validates inputs. 2. Retrieves age uncertainty via `'vaultkeeper::get_age_uncertainty()'`. 3. Pivots the wide output (one column per iteration) to long format and filters NA age estimates. 4. Joins with `'data_sample_mapping'` to attach `'dataset_name'`.

Input validation and plan construction (geographic/temporal filters, dataset type selection) are handled by `'build_vegvault_plan()'`. Only `'fossil_pollen_archive'` datasets carry per-iteration age estimates; modern plot/gridpoint datasets have no age uncertainty.

Value

A tibble with columns `'dataset_name'` (character), `'sample_name'` (character), `'iteration'` (integer), and `'age_uncertainty'` (numeric). Each row is one age-model iteration estimate for one sample. Returns an empty tibble with those columns when no age uncertainty data are available.

See Also

[[build_vegvault_plan\(\)](#)], [[extract_data_from_vegvault\(\)](#)], [[interpolate_paleo_community_with_age_uncertainty\(\)](#)]

Index

`extract_age_uncertainty_from_vegvault,`
[1](#)