

# load\_sjsdm\_available\_tier\_decisions.R

August 12, 2026

## Contents

load\_sjsdm\_available\_tier\_decisions . . . . . 1

**Index** 2

---

load\_sjsdm\_available\_tier\_decisions  
*Collect Available sjSDM Tier Decisions*

---

## Description

Discovers consecutive completed staged-round decisions in the isolated tier store. A missing next round is a normal orchestration boundary; errored targets, decision gaps, and malformed existing artifacts abort.

## Usage

```
load_sjsdm_available_tier_decisions(  
  store_path = NULL,  
  data_model_context = NULL,  
  n_non_final_rounds = NULL,  
  read_meta_function = load_targets_store_metadata,  
  read_decision_function = load_sjsdm_tier_survivor_decisions  
)
```

## Arguments

`store_path` Character scalar path to the dedicated tier-tuning targets store.

`data_model_context` One-row model-context table used to select decision rows.

`n_non_final_rounds` Non-negative integer count of rounds that publish survivor decisions.

`read_meta_function` Injectable metadata reader compatible with [load\_targets\_store\_metadata()].

`read_decision_function` Injectable decision reader compatible with [load\_sjsdm\_tier\_survivor\_decisions()].

**Value**

Ordered list of consecutive decision tibbles beginning with round one.

# Index

`load_sjsdm_available_tier_decisions`, [1](#)