

run_issue138_representative_validation.R

August 12, 2026

Contents

run_issue138_representative_validation 1

Index 3

run_issue138_representative_validation
Run an Issue 138 Representative Validation

Description

Runs staged tuning and selected final targets for one bounded validation profile through the shared sjSDM orchestration engine.

Usage

```
run_issue138_representative_validation(  
  active_config = NULL,  
  unit_pipeline = NULL,  
  tuning_target_names = NULL,  
  final_target_names = NULL,  
  store_suffix = NULL,  
  prebuild_interpolation = FALSE,  
  fresh_run = TRUE,  
  run_sequence_function = run_sjsdm_tuning_sequence,  
  run_pipeline_function = run_pipeline  
)
```

Arguments

active_config Non-default configuration profile used for the validation.

unit_pipeline Unit pipeline script passed to [run_sjsdm_tuning_sequence()].

tuning_target_names
Public v2 tuning-artifact targets included in the validation.

final_target_names
Final model and v2 evaluation-artifact targets to complete.

`store_suffix` Optional isolated spatial-unit store suffix.

`prebuild_interpolation`
 Logical controlling the first-round interpolation prebuild.

`fresh_run` Logical controlling whether the first tuning round clears its isolated target store.
 Use 'FALSE' to resume completed work items.

`run_sequence_function`
 Injectable tuning-sequence function used by tests.

`run_pipeline_function`
 Injectable pipeline runner used by tests.

Value

Invisible 'NULL'. Results are written to isolated target stores.

Index

run_issue138_representative_validation,
[1](#)