

Correct Trait Records

Description

Corrects a long-format trait-record table using human-approved correction instructions. Rows with 'action = "exclude"' are removed. Rows with 'action = "scale"' have their 'trait_value' multiplied by 'scale_factor'. Correction rows whose ('taxon_name' × 'trait_domain_name') combination does not match any record in 'data_trait_records' are reported via 'cli::cli_warn()'.

Usage

```
correct_trait_records(  
  data_trait_records,  
  data_trait_corrections,  
  verbose = TRUE  
)
```

Arguments

- | | |
|------------------------|---|
| data_trait_records | A data frame in long format with at least the columns 'taxon_name', 'trait_domain_name', and 'trait_value'. |
| data_trait_corrections | A tibble of approved corrections as returned by [validate_trait_corrections()].
Expected columns: 'taxon_name', 'trait_domain_name', 'action' ("exclude" "scale"), 'scale_factor' (numeric). |
| verbose | Logical scalar. If 'TRUE', report correction rows that do not match any trait record. |

Details

Corrections that do not match any trait record are warned about but do not cause an error. If 'data_trait_corrections' is empty, 'data_trait_records' is returned unchanged.

Value

A tibble with the same columns as 'data_trait_records', with excluded records removed and scaled records multiplied by 'scale_factor'.

See Also

```
[load_trait_corrections()], [validate_trait_corrections()], [write_trait_quality_control_report()]
```