

# load\_spatial\_resolution\_prediction\_inputs.R

August 10, 2026

## Contents

load\_spatial\_resolution\_prediction\_inputs . . . . . 1

**Index** 3

---

load\_spatial\_resolution\_prediction\_inputs  
*Read Spatial-Resolution Prediction Inputs*

---

## Description

Reads the suffixed targets needed to predict from one ‘pipeline\_paleo\_spatial\_resolution’ model resolution.

## Usage

```
load_spatial_resolution_prediction_inputs(  
  store_path,  
  resolution_id = "genus",  
  read_target_fn = targets::tar_read_raw,  
  meta_fn = targets::tar_meta,  
  include_spatial_basis = FALSE  
)
```

## Arguments

store\_path       Character scalar path to a spatial-resolution targets store.

resolution\_id    Character scalar model resolution identifier, such as “genus”.

read\_target\_fn   Function used to read targets. Defaults to [targets::tar\_read\_raw()].

meta\_fn          Function used by [load\_targets\_store\_metadata()] to read metadata.

include\_spatial\_basis   Logical scalar. When ‘TRUE’, append the additive reusable 2-D basis target.  
Default is ‘FALSE’ to preserve the existing public return schema.

## Value

Named list of model, model input, coordinate, and spatial predictor targets.

**Examples**

```
## Not run:
load_spatial_resolution_prediction_inputs(
  store_path = "Data/targets/paleo_spatial_continental/europe",
  resolution_id = "genus"
)

## End(Not run)
```

# Index

load\_spatial\_resolution\_prediction\_inputs,  
[1](#)