

prepare_classification_table_for_community_taxa.R

August 10, 2026

Contents

prepare_classification_table_for_community_taxa	1
Index	3

prepare_classification_table_for_community_taxa
<i>Prepare a classification table for community taxa</i>

Description

Re-keys a classification table so that 'sel_name' equals the classified taxon name at the specified 'vec_taxonomic_resolution', rather than the original raw pollen name. For each classified taxon name, one representative row is kept (preferring rows where the original 'sel_name' already matches the classified name). Rank columns finer than 'vec_taxonomic_resolution' are set to 'NA_character_' so that downstream 'resolve_classification_to_finetest_rank()' returns the classified name as the canonical label rather than a species name.

Usage

```
prepare_classification_table_for_community_taxa(  
  data_classification_table,  
  data_community_classified,  
  vec_taxonomic_resolution  
)
```

Arguments

- data_classification_table**
A data frame mapping raw taxon names ('sel_name') to all taxonomic rank columns ('kingdom', 'phylum', 'class', 'order', 'family', 'genus', 'species'). This is typically 'data_combined_classification_table' produced by 'pipe_segment_community_prep'.
- data_community_classified**
A data frame containing a 'taxon' column with the classified community taxon names (e.g. genus or family names). Used to determine which classified names are present in the community and should be retained in the output table.

`vec_taxonomic_resolution`

A single character string specifying the finest taxonomic rank to use for classification. Must be one of "kingdom", "phylum", "class", "order", "family", "genus", or "species".

Details

Internally, ranks from 'kingdom' up to and including 'vec_taxonomic_resolution' are used to coalesce a 'classified_name' column via 'dplyr::pick()' and 'purrr::reduce(dplyr::coalesce)'. The coalesce applies ranks from finest-to-coarsest (reversed) so that the most-specific available rank is used. After deduplication, 'sel_name' is replaced with 'classified_name' and finer rank columns are nulled out.

Value

A data frame with the same columns as 'data_classification_table' ('sel_name', 'kingdom', 'phylum', 'class', 'order', 'family', 'genus', 'species') where: - 'sel_name' is the classified taxon name (not the raw pollen name). - One row per classified taxon name (duplicate rows removed, direct-match rows preferred). - Rank columns finer than 'vec_taxonomic_resolution' are set to 'NA_character_'. - Only classified names present in 'data_community_classified' are included.

See Also

[classify_taxonomic_resolution()], [resolve_classification_to_finetest_rank()], [build_community_taxon_trait_table()]

Index

`prepare_classification_table_for_community_taxa,`
[1](#)