

prepare_spatial_variance_plot_data.R

August 10, 2026

Contents

prepare_spatial_variance_plot_data 1

Index 3

prepare_spatial_variance_plot_data
Prepare Spatial Variance Plot Data

Description

Adds shared labels and percentage columns for spatial variance partitioning figures.

Usage

```
prepare_spatial_variance_plot_data(  
  data_unit,  
  vec_scale_levels,  
  vec_resolution_labels,  
  percentage_source_column = "R2_Nagelkerke_adjusted",  
  scale_source_to_percentage = FALSE,  
  sum_over_100_action = "error"  
)
```

Arguments

data_unit Data frame with one row per spatial unit, resolution, and component. Must contain 'scale', 'resolution_id', 'component', and the column selected by 'percentage_source_column'.

vec_scale_levels Character vector giving the display order of spatial scales.

vec_resolution_labels Named character vector mapping 'resolution_id' values to display labels.

percentage_source_column Single character string naming the source percentage column. Defaults to 'R2_Nagelkerke_adjusted'.

`scale_source_to_percentage`

Logical. If 'TRUE', values from 'percentage_source_column' are multiplied by 100. Set to 'FALSE' (default) when the source column is already on a 0-100 scale.

`sum_over_100_action`

Single character string controlling behavior when grouped 'component_total_percentage' sums exceed 100. One of "error" (default), "warning", or "ignore".

Value

A tibble containing the original columns plus 'scale' as an ordered factor, 'resolution_label' as an ordered factor, 'component_label', and 'component_total_percentage'.

Index

`prepare_spatial_variance_plot_data`, [1](#)