

resolve_scale_id_from_store.R

August 10, 2026

Contents

resolve_scale_id_from_store 1

Index 3

resolve_scale_id_from_store
Get Scale ID from Current Targets Store Path

Description

Determines whether the currently active targets store corresponds to a spatial unit by inspecting the store path and checking it against the project's spatial grid CSV catalogue. Returns the 'scale_id' string for spatial pipelines, or 'NULL' for non-spatial (named-project) pipelines.

Usage

```
resolve_scale_id_from_store(  
  store = targets::tar_path_store(),  
  file = here::here("Data/Input/spatial_grid.csv")  
)
```

Arguments

store	A single character string giving the path to the targets data store. Default: 'targets::tar_path_store()', which resolves correctly both inside target commands (including callr worker processes) and when called interactively.
file	Path to the spatial grid CSV catalogue file. Default: 'here::here("Data/Input/spatial_grid.csv")'.

Details

The store path convention for spatial pipelines is: 'target_store/scale_id/pipeline_name/'. The function extracts the second-to-last path component via 'basename(dirname(store))' and checks whether it appears in the 'scale_id' column of the spatial grid CSV. For non-spatial pipelines (e.g. 'Data/targets/cz_paleo/pipeline_paleo_core/') the candidate ("project_cz_paleo") is not in the CSV, so 'NULL' is returned. When the CSV file does not exist the function returns 'NULL' gracefully.

Value

A single character string with the 'scale_id' when the store path corresponds to a spatial unit in the CSV catalogue, or 'NULL' otherwise.

See Also

load_spatial_window, load_model_tuning_parameters

Index

`resolve_scale_id_from_store`, [1](#)