

run_pipeline_units_with_status.R

August 10, 2026

Contents

run_pipeline_units_with_status 1

Index 3

run_pipeline_units_with_status
Run Pipeline Units With Status Capture

Description

Runs one isolated pipeline store per unit, continuing after unit failures while retaining an explicit status row for every requested unit.

Usage

```
run_pipeline_units_with_status(  
  scale_ids = NULL,  
  sel_script = NULL,  
  run_pipeline_function = run_pipeline,  
  progress = TRUE,  
  ...,  
  verbose = TRUE  
)
```

Arguments

scale_ids	Non-empty character vector of unique spatial unit identifiers.
sel_script	Single pipeline script path passed to 'run_pipeline_function'.
run_pipeline_function	Injectable pipeline runner called with 'sel_script', 'store_suffix', and arguments supplied through '...'. Defaults to [run_pipeline()].
progress	Logical scalar controlling the progress indicator. Defaults to 'TRUE'.
...	Additional named arguments passed to 'run_pipeline_function'.
verbose	Logical scalar controlling per-unit status messages. Defaults to 'TRUE'.

Details

This helper is intended for post-selection full-unit execution. Upstream tuning-summary production remains fail-fast so tier selection cannot use incomplete evidence.

Value

Tibble with one row per requested unit and columns 'scale_id', 'pipeline_status' ("ok" or "error"), and 'error_message'.

Examples

```
## Not run:
run_pipeline_units_with_status(
  scale_ids = c("eu_r01", "eu_r02"),
  sel_script = "R/Pipelines/pipeline_paleo_spatial_resolution.R",
  prebuild_interpolation = TRUE
)

## End(Not run)
```

Index

`run_pipeline_units_with_status`, [1](#)