Make Cross-Validation Branch Assignments

Description

Reuses a shared pre-resolution assignment for a response-resolution branch when coverage and balance remain valid, otherwise recalibrates that branch.

Usage

```
build_cross_validation_branch_assignments(
  data_locations = NULL,
  data_fold_resolution = NULL,
  data_shared_assignments = NULL,
  target_locations_per_cell = 5,
  grid_size_multipliers = 2^base::seq(-2, 2),
  n_repeats = 1L,
  occupancy_criterion = "median",
  lower_quantile_probability = 0.25,
  max_fold_location_difference = 1L,
  max_fold_sample_difference = Inf,
  seed = 900723L
)
```

Arguments

`data_locations`	Branch location table returned by [build_cross_validation_location_table()].
`data_fold_resolution`	One-row branch table returned by [resolve_cross_validation_fold_count()].
`data_shared_assignments`	Assignment table built from the shared pre-resolution sample universe.
`target_locations_per_cell`, `grid_size_multipliers`, `n_repeats`	occupancy_criterion,lower_quantile_probability, max_fold_location_difference,max_fold_sample_difference,seed Grid-calibration and assignment controls used only when branch fallback is required.

Value

Assignment tibble with the stable assignment schema. 'assignment_source' is '"shared_pre_resolution"', '"branch_fallback"', or '"branch_no_holdout"'.

Examples

```
data_locations <-
  tibble::tibble(
    location_id = base::letters[1:6],
    coord_x_km = base::seq_len(6L),
    coord_y_km = base::seq_len(6L),
    n_samples = base::rep(1L, 6L),
    row_indices = base::as.list(base::seq_len(6L))
  )
data_resolution <-
  resolve_cross_validation_fold_count(6L, 5L)
data_shared <-
  build_leave_one_location_out_assignments(data_locations)
build_cross_validation_branch_assignments(
  data_locations = data_locations,
  data_fold_resolution = data_resolution,
  data_shared_assignments = data_shared
)
```