Make Cross-Validation Grid Candidates From Fold Resolution

Description

Derives spatial-grid candidates only for spatially stratified grouped cross-validation.

Usage

```
build_cross_validation_grid_candidates_from_resolution(
  data_locations = NULL,
  data_fold_resolution = NULL,
  target_locations_per_cell = 5,
  grid_size_multipliers = 2^base::seq(-2, 2)
)
```

Arguments

`data_locations`	Location table returned by [build_cross_validation_location_table()].
`data_fold_resolution`	One-row table returned by [resolve_cross_validation_fold_count()].
`target_locations_per_cell`, `grid_size_multipliers`	Arguments passed to [build_cross_validation_grid_candidates()].

Value

Grid-candidate tibble. Gridless strategies return a zero-row tibble with the stable candidate schema.

Examples

```
data_locations <-
  tibble::tibble(
    location_id = base::letters[1:6],
    coord_x_km = base::seq_len(6L),
    coord_y_km = base::seq_len(6L),
```

```
    n_samples = base::rep(1L, 6L),
    row_indices = base::as.list(base::seq_len(6L))
  )
data_resolution <-
  resolve_cross_validation_fold_count(6L, 5L)
build_cross_validation_grid_candidates_from_resolution(
  data_locations = data_locations,
  data_fold_resolution = data_resolution
)
```