Build the sjSDM Model Input

Description

Validates that the community matrix and scaled abiotic data share the same sample rows in the same order, then bundles them — together with optional scaled spatial predictors — into the named list expected by 'fit_jsdm_model()'.

Usage

```
build_jsdm_fit_input(

  data_community_filtered = NULL,

  data_abiotic_scaled_list = NULL,

  data_spatial_scaled_list = NULL

)
```

Arguments

`data_community_filtered`	A numeric matrix with row names '"<dataset_name>__<age>"' and taxon columns, as returned by 'filter_constant_taxa()'.
`data_abiotic_scaled_list`	A named list with elements 'data_abiotic_scaled' and 'scale_attributes', as returned by 'scale_abiotic_for_fit()'. 'data_abiotic_scaled' must have row names matching those of the community matrix.
`data_spatial_scaled_list`	Optional. A named list with elements 'data_spatial_scaled' and 'spatial_scale_attributes', as returned by 'scale_spatial_for_fit()'. 'data_spatial_scaled' must have row names matching those of the community matrix. If 'NULL' (default), no spatial predictors are included.

Details

This function performs only validation and assembly; all data transformations are handled by the preceding pipeline targets. An error is raised if any two inputs differ in row count or row name ordering.

Value

A named list with three mandatory and up to two optional elements:

'data_community_to_fit'

The (filtered) community matrix.

'data_abiotic_to_fit'

The scaled abiotic data frame.

'scale_attributes'

Abiotic scaling attributes for back-transformation.

'data_spatial_to_fit'

Scaled spatial predictor data frame (only present when 'data_spatial_scaled_list' is supplied).

'spatial_scale_attributes'

Spatial scaling attributes (only present when 'data_spatial_scaled_list' is supplied).

See Also

[filter_constant_taxa()], [scale_abiotic_for_fit()], [scale_spatial_for_fit()], [fit_jsdm_model()]