Build R Architecture Dependency Map

Description

Builds deterministic Markdown describing repository R ownership, pipeline/profile/store relationships, persisted contracts, and exceptions.

Usage

```
build_r_architecture_dependency_map(
  data_scripts,
  data_functions,
  data_contracts,
  data_manifests,
  data_exceptions
)
```

Arguments

`data_scripts`	Script-path inventory data frame.
`data_functions`	Function inventory data frame.
`data_contracts`	Persisted-contract inventory data frame.
`data_manifests`	Manifest-derived profile and target inventory data frame.
`data_exceptions`	Maintained architecture-exception ledger.

Value

Character vector containing the architecture map Markdown.

Examples

```
build_r_architecture_dependency_map(
  data_scripts = tibble::tibble(
```

```
    classification = "main_analysis",
    migration_status = "migrated"
  ),
  data_functions = tibble::tibble(
    current_path = "R/Functions/example.R",
    intended_path = "R/Functions/example.R",
    migration_status = "baseline_recorded",
    callers = "R/Pipelines/_pipes/pipe_segment_example.R"
  ),
  data_contracts = tibble::tibble(
    contract_type = "literal_target",
    contract_scope = "persisted_internal"
  ),
  data_manifests = tibble::tibble(
    profile_id = "example",
    profile_role = "smoke",
    pipeline_id = "example",
    pipeline_script = "R/Pipelines/example.R",
    target_store = "Data/targets/example",
    manifest_target_count = 1L
  ),
  data_exceptions = tibble::tibble(
    exception_id = character(),
    owner_issue = character(),
    expiry_issue = character()
  )
)
```