Build One sjSDM Candidate-Fold Result

Description

Constructs one typed tuning row and its compact prediction-cache record for a completed or failed candidate lifecycle.

Usage

```
build_sjsdm_candidate_fold_result(
  data_candidate = NULL,
  list_fold_context = NULL,
  fit_seed = NA_integer_,
  score_seed = NA_integer_,
  fit_status = NULL,
  error_message = NA_character_,
  data_metrics = NULL,
  data_predicted = NULL,
  fit_seconds = NA_real_,
  prediction_seconds = NA_real_,
  scoring_seconds = NA_real_,
  data_fit_attempts = tibble::tibble(),
  converged = NA,
  actual_n_iter = NA_integer_,
  actual_n_sampling = NA_integer_,
  epochs_run = NA_integer_,
  linear_trend_slope = NA_real_,
  median_diff = NA_real_,
  early_stopping_triggered = NA
)
```

Arguments

`data_candidate`	One-row candidate table with the candidate identifier and six parameters.
`list_fold_context`	Fold context containing identifiers, sizes, and the CV strategy.
`fit_seed`, `score_seed`	Derived candidate seeds, or typed missing integers before candidate work.
`fit_status`	One of 'preparation_error', 'fit_error', 'convergence_error', 'non_converged', 'prediction_error', 'scoring_error', or 'ok'.
`error_message`	Character failure message, or a missing character value for success.
`data_metrics`	Optional named list of the five candidate scoring metrics.
`data_predicted`	Optional held-out probability matrix. Fitted model objects are never stored.
`fit_seconds`, `prediction_seconds`, `scoring_seconds`	Candidate lifecycle timings in seconds.
`data_fit_attempts`	Attempt-level CV fitting provenance, or an empty table.
`converged`, `actual_n_iter`, `actual_n_sampling`, `epochs_run`	Final-attempt convergence and actual-budget fields.
`linear_trend_slope`, `median_diff`, `early_stopping_triggered`	Final-attempt convergence diagnostics.

Value

Named list containing one-row 'data_tuning' and 'list_prediction'.