# Build sjSDM Tier Tuning Artifact

## Description

Runs compatible tier-level tuning aggregation and publishes an immutable selected-candidate artifact with complete provenance.

## Usage

```
build_sjsdm_tier_tuning_artifact(
  data_tuning_summary = NULL,
  created_at = NULL,
  include_sample_weighted = TRUE
)
```

## Arguments

| | |
|---|---|
| `data_tuning_summary` | Source-ID tuning summaries accepted by [aggregate_sjsdm_tuning_by_tier()]. |
| `created_at` | Single POSIX date-time supplied explicitly by the orchestration layer. |
| `include_sample_weighted` | Logical passed to [aggregate_sjsdm_tuning_by_tier()]. |

## Details

The artifact always selects the equal-ID result. Sample-weighted selection is retained only as a sensitivity report.

## Value

Named list containing artifact, source_candidate_loss, candidate_aggregation, and selection_sensitivity. The artifact is a one-row tibble with selected parameters, model context, source IDs, selection rule, candidate-table hash, creation time, and schema version.

## Examples

```
## Not run:
build_sjsdm_tier_tuning_artifact(
  data_tuning_summary = data_tuning_summary,
```

```
  created_at = base::as.POSIXct(
    "2026-07-05 12:00:00",
    tz = "UTC"
  )
)


## End(Not run)
```