Build an sjSDM Tuning Schedule

Description

Validates exhaustive or staged cross-validation tuning settings and builds the deterministic repeat-level candidate budget used by every model pipeline.

Usage

```
build_sjsdm_tuning_schedule(
  tuning_strategy = NULL,
  n_candidates = NULL,
  repeat_ids = NULL,
  survivor_counts = NULL,
  cv_strategy = NULL
)
```

Arguments

`tuning_strategy`	Character scalar. Either '"exhaustive"' or '"staged"'.
`n_candidates`	Positive integer number of regularization candidates.
`repeat_ids`	Unique positive integer repeat identifiers in execution order.
`survivor_counts`	Integer counts retained after each non-final staged round. Ignored for exhaustive tuning.
`cv_strategy`	Optional resolved CV strategy. Leave-one-location-out has only one unique assignment repeat, so it uses one exhaustive round even when staged tuning is configured for grouped CV.

Value

Tibble with one row per tuning round and columns 'tuning_strategy', 'strategy_version', 'round_id', 'repeat_id', 'n_candidates_entering', and 'n_candidates_surviving'.

Examples

```
build_sjsdm_tuning_schedule(
  tuning_strategy = "staged",
  n_candidates = 8L,
  repeat_ids = 1:3,
  survivor_counts = c(4L, 2L)
)
```