Build Trait Review Reconciliation

Description

Combines the mandatory trait-review queue with historical report coverage, submitted review rows, and recovered decision proposals. The result has one row per current candidate and assigns an auditable remaining-work category.

Usage

```
build_trait_review_reconciliation(
  data_trait_review_candidates,
  data_historical_review_scope,
  data_review_submission_audit,
  data_review_decision_proposals
)
```

Arguments

`data_trait_review_candidates`	Current candidate table from [build_trait_review_candidates()].
`data_historical_review_scope`	Historical report index with 'candidate_id', 'historical_report_path', 'historical_report_page', 'historical_reviewed', and the coverage basis.
`data_review_submission_audit`	Derived submission audit with 'candidate_id', 'source_row', and 'proposal_type'.
`data_review_decision_proposals`	Recovered proposal table with 'candidate_id' and 'decision_id'.

Value

A tibble containing every current candidate exactly once, historical and submission counts, proposal status, implicit no-action eligibility, and 'remaining_review_category'.

Examples

```
candidates <- tibble::tibble(
  candidate_id = "candidate-a",
```

```
  review_stage = "raw",
  taxon_name = "Taxon A",
  trait_domain_name = "Plant heigh",
  n_records = 10L,
  n_trait_names = 1L,
  n_datasets = 1L,
  n_domain_outliers = 0L,
  n_taxon_outliers = 1L,
  source_references = "",
  candidate_reasons = "taxon_outlier"
)
historical <- tibble::tibble(
  candidate_id = "candidate-a",
  historical_report_path = "report.pdf",
  historical_report_page = 2L,
  historical_reviewed = TRUE,
  historical_review_basis = "complete domain review"
)
audit <- tibble::tibble(
  candidate_id = character(),
  source_row = integer(),
  proposal_type = character()
)
proposals <- tibble::tibble(
  candidate_id = character(),
  decision_id = character()
)
build_trait_review_reconciliation(
  candidates,
  historical,
  audit,
  proposals
```

)