Build Wide-Format Species x Traits Table

Description

Pivots a long-format aggregated trait data frame into a wide-format table with one row per taxon and one column per trait domain. This produces the genus x traits matrix used for functional type assignment.

Usage

```
build_trait_table(
  data_aggregated_trait_values,
  taxon_column = "taxon_name",
  trait_domain_column = "trait_domain_name",
  trait_value_column = "trait_value_aggregated"
)
```

Arguments

`data_aggregated_trait_values`	A data frame in long format with one row per taxon x trait combination. Must contain at least the columns specified by 'taxon_column', 'trait_domain_column', and 'trait_value_column'.
`taxon_column`	A character string naming the column containing taxon (genus) names. Default: '"taxon_name"'.
`trait_domain_column`	A character string naming the column containing trait domain names. Default: '"trait_domain_name"'.
`trait_value_column`	A character string naming the column containing aggregated trait values. Default: '"trait_value_aggregated"'.

Details

Wraps 'tidyr::pivot_wider()'. If a taxon x trait combination appears more than once, only the first value is retained ('values_fn = dplyr::first').

Value

A tibble with one row per taxon and one column per trait domain, plus the taxon name column. Column names for traits are taken directly from the values in 'trait_domain_column'.

See Also

[aggregate_trait_values()], [summarise_trait_coverage()]