Build VegVault Query Plan

Description

Opens the VegVault SQLite database and constructs a lazy vaultkeepr query plan filtered to the specified dataset types, geographic bounds, and age range. The returned plan object is built up to 'vaultkeepr::select_samples_by_age()' and can be passed directly to 'extract_data_from_vegvault()' or 'extract_age_uncertainty_from_vegvault()'.

Usage

```
build_vegvault_plan(
  path_to_vegvault = here::here("Data/Input/VegVault.sqlite"),
  x_lim = NULL,
  y_lim = NULL,
  age_lim = NULL,
  sel_dataset_type = NULL
)
```

Arguments

`path_to_vegvault`	A character string specifying the path to the VegVault SQLite database (default: 'here::here("Data/Input/VegVault.sqlite")').
`x_lim`	A numeric vector of length 2 specifying the longitude range 'c(min, max)'.
`y_lim`	A numeric vector of length 2 specifying the latitude range 'c(min, max)'.
`age_lim`	A numeric vector of length 2 specifying the age range in cal yr BP 'c(min, max)'.
`sel_dataset_type`	A non-empty character vector of dataset types to include (e.g. '"fossil_pollen_archive"', 'c("vegetation_plot", "gridpoints")').

Details

The plan is assembled via the following vaultkeepr chain: 'open_vault()' -> 'get_datasets()' -> 'select_dataset_by_type()' -> 'select_dataset_by_geo()' -> 'get_samples()' -> 'select_samples_by_age()'

If vaultkeepr returns its known empty or '.' condition during plan assembly, the function raises a typed 'biodynamics_vegvault_no_records' condition. Other errors retain their original condition as the parent of a contextual error.

Value

A vaultkeepr plan object (lazy SQL query) after applying dataset type, geographic, and age-range filters, ready for use with 'extract_data_from_vegvault()' or 'extract_age_uncertainty_from_vegvault()'.

See Also

[extract_data_from_vegvault()], [extract_age_uncertainty_from_vegvault()]