Correct Trait Records

Description

Corrects a long-format trait-record table using human-approved correction instructions. Rows with 'action = "exclude"' are removed. Rows with 'action = "scale"' have their 'trait_value' multiplied by 'scale_factor'. Correction rows whose ('taxon_name' × 'trait_domain_name') combination does not match any record in 'data_trait_records' are reported via 'cli::cli_warn()'.

Usage

```
correct_trait_records(

  data_trait_records,

  data_trait_corrections,

  verbose = TRUE

)
```

Arguments

`data_trait_records`	A data frame in long format with at least the columns 'taxon_name', 'trait_domain_name', and 'trait_value'.
`data_trait_corrections`	A tibble of approved corrections as returned by [validate_trait_corrections()]. Expected columns: 'taxon_name', 'trait_domain_name', 'action' ('"exclude"' | '"scale"'), 'scale_factor' (numeric).
`verbose`	Logical scalar. If 'TRUE', report correction rows that do not match any trait record.

Details

Corrections that do not match any trait record are warned about but do not cause an error. If 'data_trait_corrections' is empty, 'data_trait_records' is returned unchanged.

Value

A tibble with the same columns as 'data_trait_records', with excluded records removed and scaled records multiplied by 'scale_factor'.

See Also

[load_trait_corrections()], [validate_trait_corrections()], [write_trait_quality_control_report()]