Assess sjSDM Candidate Guardrails

Description

Compares a tuning candidate with its reference across tuning repeats and an independent fold-local refit.

Usage

```
evaluate_sjsdm_candidate_guardrails(
  data_tuning_summary = NULL,
  data_candidate_repeat_metrics = NULL,
  data_reference_repeat_metrics = NULL,
  candidate_id = NULL,
  reference_candidate_id = NULL,
  maximum_discrimination_decrease = 0.01,
  minimum_tjur_r2 = 0.1
)
```

Arguments

`data_tuning_summary`	Repeat-by-candidate tuning summary.
`data_candidate_repeat_metrics`	Candidate repeat metrics from [summarise_sjsdm_fold_metrics()].
`data_reference_repeat_metrics`	Reference repeat metrics with the same schema as the candidate metrics.
`candidate_id`	Candidate identifier to assess.
`reference_candidate_id`	Reference identifier used for comparison.
`maximum_discrimination_decrease`	Largest allowed repeat-level decrease in AUC or Tjur R2. Defaults to '0.01'.
`minimum_tjur_r2`	Minimum candidate mean fold-macro Tjur R2. Defaults to '0.1'.

Details

Acceptance requires lower tuning NLL in every repeat, tuning AUC within the discrimination tolerance, non-inferior independent-refit AUC, Tjur R2, log loss, and Brier score in every repeat, and the scientific Tjur R2 gate.

Value

A named list containing tuning-repeat comparisons, independent-refit comparisons, and a one-row guardrail summary.

Examples

```
## Not run:

evaluate_sjsdm_candidate_guardrails(

  data_tuning_summary = data_tuning,

  data_candidate_repeat_metrics = data_candidate_metrics,

  data_reference_repeat_metrics = data_reference_metrics,

  candidate_id = "candidate_002",

  reference_candidate_id = "candidate_001"

)


## End(Not run)
```