Extract Variance Fractions from a Single sjSDM Object

Description

Extracts specified variance partitioning fractions from a single sjSDManova object, returning a two-column tibble with fraction labels and their Nagelkerke R^2 values.

Usage

```
extract_jsdm_variance_fractions(

  anova_object,

  vec_anova_fractions = base::c("F_A", "F_B", "F_S", "F_AB", "F_AS", "F_BS", "F_ABS"),

  clamp_negative = TRUE

)
```

Arguments

`anova_object`	A single sjSDManova-like list containing a named '"results"' element with columns 'models' and '"R2 Nagelkerke"'.
`vec_anova_fractions`	A non-empty character vector of fraction codes to retain (e.g. 'c("F_A", "F_B", "F_S")').
`clamp_negative`	A single logical (default 'TRUE'). If 'TRUE', negative Nagelkerke R^2 values are clamped to 0.

Details

Accesses the named '"results"' element with 'purrr::chuck()', filters the requested fraction codes, and translates them to human-readable component labels.

Value

A tibble with columns:

component

: Character. Human-readable component label (e.g. "Abiotic", "Associations", "Spatial").

R2_Nagelkerke

Numeric. Nagelkerke R^2 value for each fraction, optionally clamped to [0, Inf).

See Also

[aggregate_jsdm_variance_components()]