Load an auxiliary classification table

Description

Reads the manually curated auxiliary classification table from a CSV file. If the file does not yet exist, returns an empty tibble with the required columns so that the rest of the pipeline can continue and detect any missing taxa.

Usage

```
load_auxiliary_classification_table(

  file_auxiliary_classification_table =

    here::here("Data/Input/aux_classification_table.csv")

)
```

Arguments

`file_auxiliary_classification_table`	A length-1 character string giving the path to the CSV file. Defaults to 'here::here("Data/Input/aux_classification_table.csv")'. The file, if present, must contain a 'sel_name' column. All seven taxonomic rank columns ('kingdom', 'phylum', 'class', 'order', 'family', 'genus', 'species') are expected but optional — any that are absent are filled with 'NA_character_'.

Details

Manual classifications in this file override automatic classifications produced by 'load_taxa_classification()'. When the file exists it is validated to confirm 'sel_name' is present. Any of the seven rank columns that are absent are filled with 'NA_character_' rather than raising an error, so that partial tables (e.g., those that only specify 'family', 'genus', and 'species') continue to be accepted.

Value

A tibble with columns 'sel_name', 'kingdom', 'phylum', 'class', 'order', 'family', 'genus', and 'species' (all character). Returns an empty tibble when the file does not exist.

See Also

[build_combined_classification_table()], [validate_taxa_classification_coverage()]