Get One Model Tuning Parameter For Scale And Resolution

Description

Returns one active model-fitting tuning parameter. Spatial stores read per-scale tuning from the model tuning CSV files; non-spatial stores fall back to scalar values from 'config.yml'.

Usage

```
load_model_tuning_parameter_for_scale_and_resolution(
  param_id,
  scale_id = resolve_scale_id_from_store(),
  resolution_id = NULL,
  config_file = here::here("config.yml"),
  dir = here::here("Data/Input/Model_tuning")
)
```

Arguments

`param_id`	A single model tuning parameter name. Must be one of 'n_iter', 'n_step_size', 'n_sampling', 'n_samples_anova', or 'n_early_stopping'.
`scale_id`	Optional spatial unit identifier. Defaults to 'resolve_scale_id_from_store()'. When 'NULL', values are read from 'config.yml'.
`resolution_id`	Optional model resolution. Defaults to the active 'data_processing$taxonomic_resolution' config value. Spatial stores pass this to 'load_model_tuning_parameters()'.
`config_file`	Path to the YAML configuration file. Default: 'here::here("config.yml")'.
`dir`	Directory containing model tuning CSV files. Default: 'here::here("Data/Input/Model_tuning")'.

Value

The requested parameter value. Optional tuning parameters may return 'NULL'.

See Also

load_model_tuning_parameters