Prepare Spatial Variance Plot Data

Description

Adds shared labels and percentage columns for spatial variance partitioning figures.

Usage

```
prepare_spatial_variance_plot_data(
  data_unit,
  vec_scale_levels,
  vec_resolution_labels,
  percentage_source_column = "R2_Nagelkerke_adjusted",
  scale_source_to_percentage = FALSE,
  sum_over_100_action = "error"
)
```

Arguments

`data_unit`	Data frame with one row per spatial unit, resolution, and component. Must contain 'scale', 'resolution_id', 'component', and the column selected by 'percentage_source_column'.
`vec_scale_levels`	Character vector giving the display order of spatial scales.
`vec_resolution_labels`	Named character vector mapping 'resolution_id' values to display labels.
`percentage_source_column`	Single character string naming the source percentage column. Defaults to 'R2_Nagelkerke_adjusted'.
`scale_source_to_percentage`	Logical. If 'TRUE', values from 'percentage_source_column' are multiplied by 100. Set to 'FALSE' (default) when the source column is already on a 0-100 scale.

`sum_over_100_action`	Single character string controlling behavior when grouped 'component_total_percentage' sums exceed 100. One of '"error"' (default), '"warning"', or '"ignore"'.

Value

A tibble containing the original columns plus 'scale' as an ordered factor, 'resolution_label' as an ordered factor, 'component_label', and 'component_total_percentage'.