Render a Trait Quality-Control Report

Description

Renders 'trait_quality_control_report.qmd' to a dated PDF for one trait domain (or for all domains when 'trait_domain_filter' is 'NULL'), moves the rendered file from the Quarto docs output directory to 'path_report_directory', and compresses it in-place with 'qpdf::pdf_compress()'.

The output filename follows one of two patterns depending on 'trait_domain_filter': - 'NULL': 'trait_quality_control_report_Sys.Date().pdf' - character: 'trait_qc_<slug>_Sys.Date().pdf' where '<slug>' is 'trait_domain_filter' with all non-alphanumeric characters replaced by underscores.

Usage

```
render_trait_quality_control_report(
  trait_domain_filter = NULL,
  path_report_directory = here::here("Outputs/Reports"),
  path_report_source = here::here("R", "03_Supplementary_analyses", "Diagnostics",
    "Data_processing", "Traits", "Quality_control", "trait_quality_control_report.qmd"),
  path_render_directory = here::here("docs", "R", "03_Supplementary_analyses",
    "Diagnostics", "Data_processing", "Traits", "Quality_control"),
  maximum_pages = NULL,
  minimum_taxonomic_records = 5L,
  verbose = TRUE
)
```

Arguments

`trait_domain_filter`	Character scalar or 'NULL'. When 'NULL', all domains are rendered into a single PDF. When a character scalar, only taxa from that trait domain are included. Default: 'NULL'.
`path_report_directory`	Character scalar. Directory where the compressed PDF is saved. Default: 'here::here("Outputs/Reports")'.

`path_report_source`	Character scalar. Path to the Quarto source document. Default: 'here::here("R", "03_Supplementary_analyses", "Diagnostics", "Data_processing", "Traits", "Quality_control", "trait_quality_control_report.qmd")'.
`path_render_directory`	Character scalar. Directory that Quarto writes its output to before the file is moved. Default: 'here::here("docs", "R", "03_Supplementary_analyses", "Diagnostics", "Data_processing", "Traits", "Quality_control")'.
`maximum_pages`	Positive integer scalar or 'NULL'. Maximum number of pages to render. When 'NULL' (default) there is no cap.
`minimum_taxonomic_records`	Positive integer scalar. Minimum records per taxon required for inclusion in the taxonomic comparison panel. Default: '5L'.
`verbose`	Logical. If 'TRUE' (default), a progress message with the output path is printed to the console via 'cli::cli_inform()'. A warning is emitted via 'cli::cli_warn()' if the rendered file cannot be found.

Details

The function calls 'quarto::quarto_render()' with 'execute_params' set to 'maximum_pages', 'minimum_taxonomic_records', and 'trait_domain_filter'. The rendered file is expected at 'file.path(path_render_directory, <output_filename>)'. If found it is moved to 'path_report_directory' and compressed; if not found a warning is emitted and nothing is moved.

Value

Invisible 'NULL'. Called for its side effects: rendering and moving a PDF to 'path_report_directory'.

See Also

[write_trait_quality_control_report()]