Get Functional-Type Classification Path from Store

Description

Resolves the newest functional-type classification '.qs' file for the spatial unit encoded in a 'targets' store path.

Usage

```
resolve_functional_type_classification_path_from_store(
  store = targets::tar_path_store(),
  path_spatial_grid = here::here("Data/Input/spatial_grid.csv"),
  path_processed = here::here("Data/Processed/Traits"),
  data_source_prefix = NULL
)
```

Arguments

`store`	A single character string giving the targets store path. Default: 'targets::tar_path_store()'.
`path_spatial_grid`	Path to the spatial grid CSV catalogue file. Default: 'here::here("Data/Input/spatial_grid.csv")'.
`path_processed`	A single character string giving the directory that contains dated FT classification '.qs' files. Default: 'here::here("Data/Processed/Traits")'.
`data_source_prefix`	Optional single non-empty character string identifying a source-specific FT classification family. Use 'NULL' (default) for historical paleo/global files, or '"modern"' for modern files.

Details

The function extracts 'scale_id' from 'store', resolves the owning 'continent_id' from the spatial grid, finds matching FT classification files in 'path_processed', and returns the most recent file based on the ISO date suffix in the file name. The function errors when 'store' is not a spatial store, when no matching FT classification file exists, or when required inputs are invalid.

Value

A single character string: the path to the newest matching FT classification file for the continent that owns the spatial unit.

See Also

resolve_scale_id_from_store, resolve_continent_ids_from_scale_ids, load_latest_functional_type_classification

Examples

```
resolve_functional_type_classification_path_from_store(

  store = here::here(

    "Data/targets/paleo_spatial_regional/eu_r005/",

    "pipeline_paleo_spatial_resolution"

  )

)
```