Run an Issue 138 Representative Validation

Description

Runs staged tuning and selected final targets for one bounded validation profile through the shared sjSDM orchestration engine.

Usage

```
run_issue138_representative_validation(
  active_config = NULL,
  unit_pipeline = NULL,
  tuning_target_names = NULL,
  final_target_names = NULL,
  store_suffix = NULL,
  prebuild_interpolation = FALSE,
  fresh_run = TRUE,
  run_sequence_function = run_sjsdm_tuning_sequence,
  run_pipeline_function = run_pipeline
)
```

Arguments

`active_config`	Non-default configuration profile used for the validation.
`unit_pipeline`	Unit pipeline script passed to [run_sjsdm_tuning_sequence()].
`tuning_target_names`	Public v2 tuning-artifact targets included in the validation.
`final_target_names`	Final model and v2 evaluation-artifact targets to complete.
`store_suffix`	Optional isolated spatial-unit store suffix.
`prebuild_interpolation`	Logical controlling the first-round interpolation prebuild.

`fresh_run`	Logical controlling whether the first tuning round clears its isolated target store. Use 'FALSE' to resume completed work items.
`run_sequence_function`	Injectable tuning-sequence function used by tests.
`run_pipeline_function`	Injectable pipeline runner used by tests.

Value

Invisible 'NULL'. Results are written to isolated target stores.