Run Common sjSDM Sensitivity When Stores Are Ready

Description

Checks every enabled tier's configured representative model store before running the cross-tier common-regularization sensitivity pipeline.

Usage

```
run_sjsdm_cross_tier_sensitivity(
  profile_ids = NULL,
  pipeline_name = NULL,
  sensitivity_script = base::file.path("R", "Pipelines",
    "pipeline_sjsdm_common_regularization_sensitivity.R"),
  config_file = here::here("config.yml"),
  project_root = here::here(),
  config_load_function = load_config,
  dir_exists_function = fs::dir_exists,
  run_pipeline_function = run_pipeline
)
```

Arguments

`profile_ids`	Non-empty character vector of unique spatial configuration profile IDs.
`pipeline_name`	Single spatial-resolution pipeline directory name.
`sensitivity_script`	Common-regularization sensitivity pipeline script path.
`config_file`	Configuration file passed to 'config_load_function'.
`project_root`	Project root used to resolve configured relative target-store paths.
`config_load_function`	Injectable complete-configuration loader. Defaults to [load_config()].

`dir_exists_function` Injectable directory-existence predicate. Defaults to [fs::dir_exists()].

`run_pipeline_function` Injectable pipeline runner. Defaults to [run_pipeline()].

Details

The sensitivity pipeline is an all-tier operation. It is not started unless every configured representative store exists, so a standalone local runner can finish without failing on absent continental or regional stores.

Value

Tibble with one row per requested profile, its representative store status, and a sensitivity status of '"completed"', '"skipped_missing_store"', or '"skipped_disabled"'.

Examples

```
## Not run:

run_sjsdm_cross_tier_sensitivity(

  profile_ids = c(

    "project_paleo_spatial_continental",

    "project_paleo_spatial_regional",

    "project_paleo_spatial_local"

  ),

  pipeline_name = "pipeline_paleo_spatial_resolution"

)


## End(Not run)
```