Run One Prepared sjSDM Tuning Candidate

Description

Fits, predicts, and scores one regularization candidate against one previously prepared cross-validation fold.

Usage

```
run_sjsdm_prepared_tuning_candidate(
  data_candidate = NULL,
  list_prepared_fold = NULL,
  list_fold_context = NULL,
  fit_function = NULL,
  predict_function = NULL,
  score_function = score_sjsdm_tuning_predictions,
  seed = 900723L,
  epsilon = 1e-06
)
```

Arguments

`data_candidate`	One-row candidate table with candidate ID and six regularization values.
`list_prepared_fold`	Prepared fold containing train input, test input, and observed test data.
`list_fold_context`	Fold identifiers, sample/location counts, and cross-validation strategy.
`fit_function`, `predict_function`, `score_function`	Injectable fitting, prediction, and scoring functions.
`seed`	Non-negative base integer used to derive fit and score seeds.
`epsilon`	Probability clipping tolerance passed to the score function.

Value

Named list containing one-row 'data_tuning' and compact 'list_prediction' output without a fitted model object.

Examples

```
## Not run:

run_sjsdm_prepared_tuning_candidate(

  data_candidate = data_candidate,

  list_prepared_fold = list_prepared_fold,

  list_fold_context = list_fold_context,

  fit_function = fit_sjsdm_model,

  predict_function = predict_sjsdm_model

)


## End(Not run)
```